

## MovieBird MB12 „MiniBird”



The all-new MovieBird MB12 „MiniBird” is a lightweight and agile two section telescopic camera crane. It’s small size and robust construction make it a versatile crane capable of being mounted on a number of platforms

including the all new MovieBird scissor dolly, a heavy duty camera dolly, an electric camera car etc.

The crane features novel triangular cross section with an innovative three-point guide rail system which, together with extruded aluminum sections make it a highly stable and robust platform capable of withstanding stresses and shocks while moving on a vehicle.

The MiniBird also features a new levelling head with over-slung and under-slung capability, buttons for adjustable level offset and optional Gyroscopic Levelling Add-on [GLA]. The optional all-new MovieBird scissor dolly with folding arms allows to change the width for different track systems. In its most compact configuration it allows to move the crane through small office doors (0,8m).

### Moviebird 12 Technical Specifications\*

Max. nose load	60 kg	132 lbs
Max. extension speed	1.62 m/s	5.3 ft/s
Max. reach	3.66 m	12,0 ft
Telescopic range	2,60 m	8.5 ft
Overall length	2.45 m	8,0 ft
Min. arm weight	90 kg	200 lbs
Fully loaded arm weight	400 kg	880 lbs
Base weight:	150 kg	330 lbs
One counterweight:	11.3 kg	24.8 lbs
Counterweights:	250 kg	550 lbs
Crane weight incl. counterweight:	550 kg	1210 lbs

\* Specifications may change at any time

### Power supply:

- The MovieBird MB12 can be powered off batteries and mains. Supply Voltage: 48-55 VDC.
- The crane comes equipped with: 110-240 VAC Power supply unit, cable for connecting external battery.

